

ASX ANNOUNCEMENT AND MEDIA RELEASE

24 July 2015

99m GOLD ZONE AND CURRENT DRILL HOLE ARE SIMILAR
HIGHLIGHTS

- Current drill hole 600m north along strike has now been completed on Namdini Extension
- This drill hole is located a further 200m north along strike from the 99m gold zone
- Samples submitted to the laboratory for express processing

Cardinal Resources Limited (ASX: CDV) ("Cardinal" or "the Company") is pleased to announce that drilling has been completed a further 200m north along strike within the recently acquired area of the Namdini Mining Licence ("Namdini"), located within Cardinal's Namdini Project in Ghana (see Figure 1).

Commenting from Ghana, Cardinal Resources Managing Director Archie Koimtsidis said:

"Drill hole NMRC490-782, located 600m north along strike, has been completed and samples submitted to the laboratory for express processing.

"We anticipate that this drill hole could yield results as encouraging as the 99m mineralised drill hole, see 2 July 2015 ASX announcement, which is located 200m south along strike (see Figure 2).

"The RC drill chips from both drill holes have similar lithologies and contain similar disseminated pyrite grains. The full potential of this granitoid is yet to be evaluated as this drill hole had to be stopped due to surface caving. The disseminated pyrite grains were still visible when the drill hole was stopped.

"We expect that this drill hole should further increase the gold inventory within the Namdini Project."




Figure 1: Namdini Project Proximity Map

Cardinal Resources Limited ABN 56 147 325 620

www.cardinalresources.com.au

Ghana: Durugu Residential Area, Kumbosco, Bolgatanga, Ghana P: +233 (0) 261905220 SKYPE: cardinal.archie

Australia: Level 1, 115 Cambridge Street, West Leederville, Perth, 6007 P: +61 (8) 9322 6600 F: +61 (8) 9322 6610




Figure 2: Drill Hole NMRC490-782, 600m NNE of Confirmed Mineralised Zone

RC DRILL CHIPS

The RC drill chips from drill hole NMRC490-782 are comprised of both volcaniclastic and monzonite granitoid lithologies (see Figure 3 and Appendix), which are similar to the drill chips found in the 99m mineralised drill hole 200m south along strike.




Figure 3: Drill Hole NMRC490-782 Section

Volcaniclastics

The volcaniclastic chips are medium to fine grained, with variable light grey to light green colours. The green colours are due to hydrothermal alteration by carbonate, silica, sericite, chlorite and epidote. Finely disseminated pyrite grains occur within the altered volcaniclastics.

Quartz Veins

Quartz veins with pyrite are developed on the contact between the volcaniclastics and the granitoids.

Monzonite Granitoids

The monzonite granitoid chips are coarse grained, with cream, light buff and greenish colours containing thin quartz vein stockworks and disseminated pyrite. The light greenish colour of the drill chips is due to hydrothermal alteration to epidote, sericite and minor chlorite.

MONITORING OF DRILLING PROGRAMS

Cardinal's technical and management team evaluates all of the available data on a daily basis with the main focus being the expansion of the gold potential for the expanded licence areas.

Cardinal is the owner and operator of its own drill rig and has established an express assaying service with its drilling results, enabling the Company to continually improve its drill plan strategy as new information becomes available.

The Company will continue drilling selective holes, submitting the samples and be on standby as results are received. Once the results have been assessed, Cardinal can plan further drill holes to maximise expansion of the gold inventory within the Namdini Project.

For further information contact:

Archie Koimtsidis
Managing Director
Cardinal Resources Limited
P: +233 (0)26 190 5220
Skype: cardinal.archie

APPENDIX
COMPARISON OF NMRC452-770 AND NMRC490-782 DRILL HOLES

Tsp = Transported Soils; **Sap** = Saprolite; **Tsn** = Transition (weathered rock)

Vcl = Volcaniclastic; **Gtd** = Monzonite Granitoid; **QV** = Quartz Veins

Fro m (m)	To (m)	NMRC 452 – 770 Lithology Code	NMRC 490 – 782 Lithology Code
0	1	Tsp	Tsp
1	2	Sap	Tsp
2	3	Sap	Sap
3	4	Sap	Sap
4	5	Sap	Sap
5	6	Sap	Sap
6	7	Sap	Sap
7	8	Tsn	Sap
8	9	Tsn	Sap
9	10	Tsn	Tsn
10	11	Tsn	Tsn
11	12	Tsn	Tsn
12	13	Tsn	Tsn
13	14	Tsn	Tsn
14	15	Tsn	Tsn
15	16	Tsn	Tsn
16	17	Tsn	Tsn
17	18	Tsn	Tsn
18	19	Tsn	Tsn
19	20	Gtd	Tsn
20	21	Gtd	Tsn
21	22	Gtd	Vcl
22	23	Gtd	Vcl
23	24	Gtd	Vcl
24	25	Gtd	Vcl
25	26	Gtd	Vcl
26	27	Gtd	Vcl
27	28	Gtd	Vcl
28	29	Gtd	Vcl
29	30	Gtd	Vcl
30	31	Gtd	Vcl
31	32	Gtd	Vcl
32	33	Gtd	Vcl
33	34	Gtd	Vcl
34	35	Gtd	Vcl
35	36	Gtd	Vcl
36	37	Gtd	Vcl

37	38	Gtd		Vcl
38	39	Gtd		Vcl
39	40	Gtd		Vcl
40	41	Gtd		Vcl
41	42	Gtd		Vcl
42	43	Gtd		Vcl
43	44	Gtd		Vcl
44	45	Gtd		Vcl
45	46	Gtd		Vcl
46	47	Gtd		Vcl
47	48	Gtd		Vcl
48	49	Gtd		QV
49	50	Gtd		QV
50	51	Gtd		Gtd
51	52	Gtd		Gtd
52	53	Gtd		Gtd
53	54	Gtd		Gtd
54	55	Gtd		Gtd
55	56	Gtd		Gtd
56	57	Gtd		Gtd
57	58	Gtd		Gtd
58	59	Gtd		Gtd
59	60	Gtd		Gtd
60	61	Gtd		Gtd
61	62	Gtd		Gtd
62	63	Gtd		Gtd
63	64	Gtd		Gtd
64	65	Gtd		Gtd
65	66	Gtd		Gtd
66	67	Gtd		Gtd
67	68	Gtd		Gtd
68	69	Gtd		Gtd
69	70	Gtd		Gtd
70	71	Vcl		Gtd
71	72	Vcl		Gtd
72	73	Vcl		Gtd
73	74	Vcl		Gtd
74	75	Vcl		Gtd
75	76	Vcl		Gtd
76	77	Vcl		Gtd
77	78	Vcl		Gtd
78	79	Vcl		Gtd
79	80	Vcl		Gtd
80	81	Gtd		Gtd
81	82	Gtd		Gtd
82	83	Gtd		Gtd
83	84	Gtd		Gtd
84	85	Gtd		Gtd
85	86	Gtd		Gtd

Cardinal Resources Limited ABN 56 147 325 620

www.cardinalresources.com.au

Ghana: Durugu Residential Area, Kumbosco, Bolgatanga, Ghana P: +233 (0) 261905220 SKYPE: cardinal.archie

Australia: Level 1, 115 Cambridge Street, West Leederville, Perth, 6007 P: +61 (8) 9322 6600 F: +61 (8) 9322 6610

86	87	Gtd		Gtd
87	88	Gtd		Gtd
88	89	Gtd		Gtd
89	90	Gtd		Gtd
90	91	Gtd		Gtd
91	92	Gtd		Gtd
92	93	Gtd		Gtd
93	94	Gtd		Gtd
94	95	Gtd		Gtd
95	96	Gtd		Gtd
96	97	Gtd		Gtd
97	98	Gtd		Gtd
98	99	Gtd		Gtd
99	100	-		Gtd
100	101	-		Gtd
101	102	-		Gtd
102	103	-		Gtd

Tsp = Transported Soils; **Sap** = Saprolite; **Tsn** = Transition (weathered rock)

Vcl = Volcaniclastic; **Gtd** = Monzonite Granitoid; **QV** = Quartz Veins

Competent Person's Statement

Information in this report that relates to the Namdini Project is based on information compiled by **Mr Paul Abbott**, a full time employee of Cardinal Resources Limited, who is a Fellow of the Australasian Institute of Mining and Metallurgy and a Member of the Geological Society of South Africa. Mr Abbott has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person, as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr Abbott consents to the inclusion in this report of the statements based on his information in the form and context in which it appears.

Disclaimer

This ASX announcement (Announcement) has been prepared by Cardinal Resources Limited (ABN: 56 147 325 620) ("Cardinal" or "the Company"). It should not be considered as an offer or invitation to subscribe for or purchase any securities in the Company or as an inducement to make an offer or invitation with respect to those securities. No agreement to subscribe for securities in the Company will be entered into on the basis of this Announcement.

This Announcement contains summary information about Cardinal, its subsidiaries and their activities which is current as at the date of this Announcement. The information in this Announcement is of a general nature and does not purport to be complete nor does it contain all the information which a prospective investor may require in evaluating a possible investment in Cardinal.

By its very nature exploration for minerals is a high risk business and is not suitable for certain investors. Cardinal's securities are speculative. Potential investors should consult their stockbroker or financial advisor. There are a number of risks, both specific to Cardinal and of a general nature which may affect the future operating and financial performance of Cardinal and the value of an investment in Cardinal including but not limited to economic conditions, stock market fluctuations, gold price movements, regional infrastructure

Cardinal Resources Limited ABN 56 147 325 620

www.cardinalresources.com.au

Ghana: Durugu Residential Area, Kumbosco, Bolgatanga, Ghana P: +233 (0) 261905220 SKYPE: cardinal.archie

Australia: Level 1, 115 Cambridge Street, West Leederville, Perth, 6007 P: +61 (8) 9322 6600 F: +61 (8) 9322 6610

constraints, timing of approvals from relevant authorities, regulatory risks, operational risks and reliance on key personnel and foreign currency fluctuations.

Certain statements contained in this announcement, including information as to the future financial or operating performance of Cardinal Resources and its projects, are forward-looking statements that:

- may include, among other things, statements regarding targets, estimates and assumptions in respect of mineral reserves and mineral resources and anticipated grades and recovery rates, production and prices, recovery costs and results, capital expenditures, and are or may be based on assumptions and estimates related to future technical, economic, market, political, social and other conditions;
- are necessarily based upon a number of estimates and assumptions that, while considered reasonable by Cardinal Resources, are inherently subject to significant technical, business, economic, competitive, political and social uncertainties and contingencies; and,
- involve known and unknown risks and uncertainties that could cause actual events or results to differ materially from estimated or anticipated events or results reflected in such forward-looking statements.

Cardinal Resources disclaims any intent or obligation to update publicly any forward-looking statements, whether as a result of new information, future events or results or otherwise. The words 'believe', 'expect', 'anticipate', 'indicate', 'contemplate', 'target', 'plan', 'intends', 'continue', 'budget', 'estimate', 'may', 'will', 'should', 'inventory', 'schedule' and similar expressions identify forward-looking statements.

All forward looking statements made in this announcement are qualified by the foregoing cautionary statements. Investors are cautioned that forward-looking statements are not guarantees of future performance and accordingly investors are cautioned not to put undue reliance on forward-looking statements due to the inherent uncertainty therein.

No verification: Although all reasonable care has been undertaken to ensure that the facts and opinions given in this Announcement are accurate, the information provided in this Announcement has not been independently verified.

JORC CODE 2012 EDITION – TABLE 1
99m GOLD ZONE AND CURRENT DRILL HOLE ARE SIMILAR
Section 1 – Sampling Technique and Data

Criteria	JORC Code Explanation	Commentary
Sampling techniques	<p>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</p> <p>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</p> <p>Aspects of the determination of mineralisation that are Material to the Public Report.</p> <p>In cases where ‘industry standard’ work has been done this would be relatively simple (eg ‘reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay’). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</p>	<p>Nature and quality of sampling is carried out under QAQC procedures as per industry standards, with duplicates taken every 22nd sample, while standards and blanks are inserted in the ratio of 1:22.</p> <p>Sample representivity is ensured through a 3 tier riffle splitter, as it provides an unbiased sample.</p> <p>The determination of mineralisation is not yet known.</p> <p>Industry standard reverse circulation drilling was used to obtain 1m samples from which 3 kg was pulverised to produce a 50 g charge for fire assay.</p>
Drilling techniques	Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	Reverse Circulation drilling with a standard tube, Remet 5½ inch Hard Face (face-sampling) button drilling bit.
Drill sample recovery	<p>Method of recording and assessing core and chip sample recoveries and results assessed.</p> <p>Measures taken to maximise sample recovery and ensure representative nature of the samples.</p> <p>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</p>	<p>Method of recording and assessing chip samples was on a hand held Motion F5te Tablet PC using a set of standard templates supplied by Maxwell Geoservices, Perth (Maxwell).</p> <p>The measures taken to maximize sample recovery are through a cyclone and a 3 tier riffle splitter. This method ensures maximum sample recovery and an unbiased representative sample to be assayed.</p> <p>No relationship is known to exist between sample recovery and grade, and no sample bias may have occurred due to preferential loss/gain of any fine/coarse material.</p>
Logging	<p>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</p> <p>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</p>	Chip samples have been geologically logged to a level of detail to support appropriate future Mineral Resource estimations.
		Logging is quantitative. Chip samples are photographed both in dry and wet form.

Criteria	JORC Code Explanation	Commentary
	The total length and percentage of the relevant intersections logged.	All holes are logged in full.
Sub-sampling techniques and sample preparation	<p>If core, whether cut or sawn and whether quarter, half or all core taken.</p> <p>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</p> <p>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</p>	<p>No core has been drilled.</p> <p>The sub-sampling technique is with a 3 tier riffle splitter, and sampled dry.</p> <p>Sample preparation is completed at SGS Laboratories, Ouagadougou, Burkina Faso. All preparation equipment is flushed with barren material prior to the commencement of sample preparation. The entire sample is dried, crushed to a nominal 2mm using a Jaw Crusher, then <1.5 kg is split using a Jones type riffle. The reject sample is retained in the original sample bag. The split is pulverised in a LM2 grinding mill to a nominal 85% passing 75 micron size fraction. An approximate 200 gram sub-sample split is taken for fire assay with the pulverized residue retained in a plastic bag. The pulverized split is fire assayed by standard procedures with an AAS finish to 10 ppb detection limit. Both the remaining reject and pulverized samples are returned and stored at Cardinal's Bolgatanga premises.</p>
	Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.	Quality control procedures adopted for all sub-sampling stages to maximize representivity of samples uses commercial certified reference material (CRM) for standards.
	Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.	Measures taken to ensure that the sampling is representative of the in situ material collected are to insert duplicates at every 22nd sample. Approximately 3kg samples from the splitter are retained from each sample and stored on the company's premises for possible re-assay.
	Whether sample sizes are appropriate to the grain size of the material being sampled.	The sample sizes are considered appropriate to give an accurate indication of gold mineralisation.
Quality of Assay data and laboratory tests	<p>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</p>	<p>The pulverized rock sample is weighed and mixed with flux and fused using lead oxide at 1,100°C, followed by cupellation of the resulting lead button (Dore bead). The bead is digested using 1:1 HNO₃ and HCl and the resulting solution is submitted for analysis.</p> <p>The digested sample solution is aspirated into the Flame Atomic Absorption Spectrometer (AAS), aerosolised, and mixed with the combustible gas, acetylene and air. The mixture is ignited in a flame whose temperature ranges from 2,100 to 2,800°C. During combustion, atoms of the gold in the sample are reduced to free, unexcited ground state atoms, which absorb light. Light of the appropriate wavelength is supplied and the amount of light absorbed can be measured against a standard curve.</p>
	Results have a lower gold detection limit of 10 ppb.	

Criteria	JORC Code Explanation	Commentary
		The AAS equipment is calibrated with each job.
		The analytical technique is industry standard fire assay which is considered to be a total digest of gold.
	For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.	No hand held geophysical tools are used.
	Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.	Sample preparation checks for fineness are carried out by the laboratory as part of their internal procedures to ensure the grind size of 85-90% passing 75 micron is being attained. Each batch of 100 samples has 5 checks (20%), with the grind size varying between 87-99% passing 75 micron, which is acceptable. Laboratory QAQC involves the use of internal lab standards using certified reference material and blanks.
		Certified reference materials, having a range of values, and in-house blanks are inserted in the ratio of 1:22. Duplicate samples are taken every 22nd sample.
		External laboratory checks are done on a three monthly basis through Laboratories Quality Services International (LQSI). Recent LQSI checks of Fire Assay analyses on Low Grade Oxide Material produced acceptable levels of accuracy and precision.
Verification of sampling and assaying	The verification of significant intersections by either independent or alternative company personnel.	The verification of significant intersections by either independent or alternative company personnel has not occurred.
	The use of twinned holes.	There has been no use of twinned holes.
	Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.	Primary data was collected on a hand held Motion F5te Tablet PC using a set of standard templates supplied by Maxwell Geoservices, Perth (Maxwell). Daily data was synchronised and digitally captured by Maxwell for validation and compilation into Excel and Access spreadsheets and stored on the Cardinal servers located in Bolgatanga, Ghana, West Africa.
	Discuss any adjustment to assay data.	No adjustments were made to assay data.
Location of data points	Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.	Accuracy of drill hole collar surveys is +/- 3m using a hand held Garmin GPSmap 62s GPS.
	Specification of the grid system used.	WGS84 Sector 30N, with local grid baseline at 010° True North and lines at 50m to 100m intervals and stations at 50m along lines.
	Quality and adequacy of topographic control.	The quality and adequacy of topographic control is +/- 3m using a hand held Garmin GPSmap 62s GPS.
Data spacing and distribution	Data spacing for reporting of Exploration Results.	Data spacing is 50-100m (northing) and 20-30m (easting).
	Whether the data spacing and distribution is sufficient to establish the degree of geological and	The data spacing and distribution is considered to be sufficient to establish a degree of geological and grade

Criteria	JORC Code Explanation	Commentary
	grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.	continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.
Orientation of data in relation to geological structure	Whether sample compositing has been applied.	No sample compositing has been applied.
	Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.	The orientation of sampling achieves unbiased sampling of possible structures as drilling is orientated normal to the dip and foliation of the deposit.
	If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.	No orientation based sampling bias has been identified in the data to date.
Sample security	The measures taken to ensure sample security.	The measures taken to ensure sample security are through an independent Ghanaian security contractor. Samples are stored at Cardinal's base camp located at Bolgatanga, Ghana, West Africa under security until collected by SGS Laboratories and transported to their Ouagadougou laboratory in Burkina Faso.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	Sampling techniques are of industry standards. Data is audited by Maxwell Geoservices (Perth), who have not made any other recommendations.

Section 2 – Reporting of Exploration Results

(Criteria listed in section 1 will also apply to this section where relevant)

Criteria	JORC Code Explanation	Commentary
Mineral Tenement and Land Status	Type, name/reference number, location and ownership including agreements or material issues with third parties including joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.	The Namdini Mining Licence is located in NE Ghana. Namdini Mining Limited (NML) holds the mining licence. NML signed a Heads of Agreement with Savannah Mining Ltd (Savannah) to provide "Mining Support" services to NML. Savannah has signed a Heads of Agreement with Cardinal Mining Services Ltd (CMS) to provide "Mining Support" services in relation to the Namdini Mining Licence.
	The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.	There are no known impediments to offer "Mining Support" services to Namdini Mining Limited within the Namdini Mining licence area.
Exploration Done by Other Parties	Acknowledgment and appraisal of exploration by other parties.	No previous systematic exploration has been undertaken.
Geology	Deposit type, geological setting and style of mineralisation	The deposit type comprises gold mineralisation within sheared and highly altered rocks containing sulphides (pyrite and arsenopyrite). The geological setting is a Paleoproterozoic

Criteria	JORC Code Explanation	Commentary
		Greenstone Belt comprising Birimian metavolcanics, volcaniclastics & metasediments located in close proximity to a major 30 km ~N-S regional shear zone with splays.
		The style of mineralisation is hydrothermal alteration containing disseminated gold-bearing sulphides
Drill hole information	<p>A summary of all information material to the understanding of the exploration results including tabulation of the following information for all Material drill holes:</p> <ul style="list-style-type: none"> • Easting and northing of the drill hole collar • Elevation or RL (Reduced Level – elevation above sea level in meters) of the drill hole collar • Dip and azimuth of the hole • Down hole length and interception depth • Hole length 	A summary of all information is contained within this announcement.
	If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.	There has been no exclusion of information.
Data aggregation methods	<p>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.</p>	No weighting averaging techniques nor cutting of high grades have yet been undertaken.
	Where aggregated intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.	Aggregated intercepts incorporating short lengths of high grade will be calculated and will include no more than intervals of 3m below cut-off grades of 0.5 g/t Au.
	The assumptions used for any reporting of metal equivalent values should be clearly stated.	No metal equivalent values were used for this report.
Relationship between mineralisation widths and intercept lengths	<p>These relationships are particularly important in the reporting of exploration results.</p>	The relationship between mineralisation widths and intercept lengths is not yet known.
	<p>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</p>	The geometry of the mineralisation with respect to the drill hole angle is not yet known.
	<p>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known').</p>	Only down hole lengths are reported and true widths of mineralisation are not yet known.
Diagrams	<p>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plane view of drill hole collar locations and appropriate sectional views.</p>	An appropriate plan view is included in this announcement.

Criteria	JORC Code Explanation	Commentary
Balanced Reporting	Where comprehensive reporting of all Exploration Results is not practical, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	Only the lithological data is contained within the Appendix of this announcement.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observation; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	The interpretation of the geological observations shown in Figure 2 is subject to possible change as new information is gathered.
Further Work	<p>The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large – scale step – out drilling).</p> <p>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</p>	<p>A combination of reverse circulation and diamond drilling is planned, followed by possible additional ground geophysical surveys depending on the results of the drilling.</p> <p>The plan included shows the possible extent of mineralisation based on geological observations and previous assay results. Future drilling is planned north and west of the Namdini Licence to obtain strike and down dip extensions to the ore bodies.</p>